

Interflon Lube EPR

Version number:
1.1
Replaces version:

Date of issue
2026-04-15

Revision:
2026-04-15.

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Trade name **Interflon Lube EPR**
Registration number (REACH) not relevant (mixture)
Unique formula identifier - UFI JH50-Y0MC-A00Q-0139

1.2 Relevant identified uses of the substance or mixture and uses advised against

Relevant identified uses Industrial use
Scope lubricant

1.3 Details of the supplier of the safety data sheet

Interflon BV
Belder 47
4704 RK Roosendaal
Netherlands

Telephone: +31 (0)165 553911
e-mail: Service@Interflon.com
Website: www.Interflon.com

Supplier (importer)

Interflon Ireland
Telephone:

e-mail (competent person) msds.ie@interflon.com

1.4 Emergency telephone number

Poison centre			
Name	Street	City	Telephone
Poisons Information Centre of Ireland	Beaumont Hospital, Beaumont	Dublin	Members of Public: +353 (1) 809 2166. (8.00 a.m. to 10.00 p.m. 7 days a week) Healthcare Professionals: +353 (1) 809 2566 (24 hour service)

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Classification according to Regulation (EC) No 1272/2008 (CLP)

Section	Hazard class	Category	Hazard class and category	Hazard statement
3.3	serious eye damage/eye irritation	2	Eye Irrit. 2	H319

For full text of abbreviations: see SECTION 16.

2.2 Label elements

Labelling according to Regulation (EC) No 1272/2008 (CLP)

- Signal word. warning

Interflon Lube EPR

Version number: 1.1

date of issue
2026-04-15

Date of compilation: Revision: 2026-04-15

- Pictograms

GHS07



- Hazard statements

H319 Causes serious eye irritation.

- Precautionary statements

P280 Wear protective gloves/protective clothing/eye protection/face protection/hearing protection/....

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P337+P313 If eye irritation persists: Get medical advice/attention.

- Supplemental hazard information

EUH066 Repeated exposure may cause skin dryness or cracking.

EUH208 Contains Sulfonic acids, petroleum, calcium salts. May produce an allergic reaction.

2.3 Other hazards

This material is combustible, but will not ignite readily. This mixture does not contain any substances that are assessed to be a PBT or a vPvB.

Results of PBT and vPvB assessment

Does not contain a PBT-/vPvB-substance at a concentration of $\geq 0,1\%$.

Endocrine disrupting properties

Does not contain an endocrine disruptor (ED) at a concentration of $\geq 0,1\%$.

SECTION 3: Composition/information on ingredients

3.1 Substances

Not relevant (mixture)

3.2 Mixtures

Product description

Mixture of mineral and vegetable oils, additives and Micpol®

Hazardous ingredients

Name of substance	Identifier	Wt%	Classification acc. to GHS	Notes
Hydrocarbons, C10-C13, n-alkanes, isoalkanes, cyclics, < 2% aromatics	CAS No 64742-48-9 EC No 918-481-9 Index No 649-327-00-6 REACH Reg. No 01-2119457273-39-xxxx	25 - < 50	Asp. Tox. 1 / H304	L(b)
N-methyl-N-[C18-(unsaturated)alkanoyl]glycine	EC No 701-177-3 REACH Reg. No 01-2119488991-20-xxxx	1 - < 5	Acute Tox. 4 / H332 Skin Irrit. 2 / H315 Eye Dam. 1 / H318 Aquatic Acute 1 / H400 Aquatic Chronic 3 / H412	
Sulfonic acids, petroleum, calcium salts	CAS No 61789-86-4 EC No	< 1	Skin Sens. 1B / H317	

Interflon Lube EPR

Version number: 1.1

date of issue
2026-04-15

Date of compilation: Revi-
sion: 2026-04-15

Name of substance	Identifier	Wt%	Classification acc. to GHS	Notes
	263-093-9 REACH Reg. No 01-2119488992-18-xxxx			

Notes

L(b): The classification as a carcinogen is not required. The substance contains less than 3 % DMSO extract

Concentration limit, M-Factor, ATE

Hazardous ingredients, Specific Conc. Limits, M-factors, ATE				
Name of substance	Specific Conc. Limits	M-Factors	ATE	Exposure route
N-methyl-N-[C18-(unsaturated)alkanoyl]glycine	-	-	11 mg _i /4h 1.37 mg _j /4h	inhalation: vapour inhalation: dust/mist
Sulfonic acids, petroleum, calcium salts	Skin Sens. 1B; H317: C ≥ 10 %	-	-	

Remarks

For full text of Hazard- and EU Hazard-statements: see SECTION 16.

SECTION 4: First aid measures

4.1 Description of first aid measures

General notes

Do not leave affected person unattended. Remove victim out of the danger area. Keep affected person warm, still and covered. Take off immediately all contaminated clothing. In all cases of doubt, or when symptoms persist, seek medical advice. In case of unconsciousness place person in the recovery position. Never give anything by mouth.

Following inhalation

If breathing is irregular or stopped, immediately seek medical assistance and start first aid actions. Provide fresh air.

Following skin contact

Wash with plenty of soap and water.

Following eye contact

Remove contact lenses, if present and easy to do. Continue rinsing. Irrigate copiously with clean, fresh water for at least 10 minutes, holding the eyelids apart.

Following ingestion

Rinse mouth with water (only if the person is conscious). Do NOT induce vomiting.

4.2 Most important symptoms and effects, both acute and delayed

Symptoms and effects are not known to date.

4.3 Indication of any immediate medical attention and special treatment needed

none

SECTION 5: Firefighting measures

5.1 Extinguishing media

Suitable extinguishing media

Water spray, Water mist, Fire extinguishing powder, Carbon dioxide (CO₂), Carbon dioxide (CO₂), Alcohol resistant foam

Unsuitable extinguishing media

Water jet

5.2 Special hazards arising from the substance or mixture

Interflon Lube EPR

Version number: 1.1

date of issue
2026-04-15

Date of compilation: Revi-
sion: 2026-04-15

Hazardous combustion products
Nitrogen oxides (NOx), Carbon monoxide (CO), Carbon dioxide (CO₂)

5.3 Advice for firefighters

In case of fire and/or explosion do not breathe fumes. Co-ordinate firefighting measures to the fire surroundings. Do not allow firefighting water to enter drains or water courses. Collect contaminated firefighting water separately. Fight fire with normal precautions from a reasonable distance. Use suitable breathing apparatus.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

For non-emergency personnel
Remove persons to safety.

For emergency responders
Wear breathing apparatus if exposed to vapours/dust/spray/gases.

6.2 Environmental precautions

Keep away from drains, surface and ground water. Retain contaminated washing water and dispose of it.

6.3 Methods and material for containment and cleaning up

Advice on how to contain a spill
Covering of drains

Advice on how to clean up a spill

Wipe up with absorbent material (e.g. cloth, fleece). Collect spillage: sawdust, kieselgur (diatomite), sand, universal binder

Appropriate containment techniques
Use of adsorbent materials.

Other information relating to spills and releases
Place in appropriate containers for disposal. Ventilate affected area.

6.4 Reference to other sections

Hazardous combustion products: see section 5. Personal protective equipment: see section 8. Incompatible materials: see section 10. Disposal considerations: see section 13.

SECTION 7: Handling and storage

7.1 Precautions for safe handling

Recommendations

- Measures to prevent fire as well as aerosol and dust generation
Use local and general ventilation. Use only in well-ventilated areas.

Advice on general occupational hygiene

Remove contaminated clothing and protective equipment before entering eating areas. Never place chemicals in containers that are normally used for food or drink.

7.2 Conditions for safe storage, including any incompatibilities

Conditions of storage

Store in accordance with local/regional/national/international regulations. Keep container tightly closed and in a well-ventilated place.

Managing of associated risks

- Flammability hazards
Keep in a cool place.

7.3 Specific end use(s)

See section 16 for a general overview.

Interflon Lube EPR

Version number: 1.1

date of issue
2026-04-15

Date of compilation: Revi-
sion: 2026-04-15

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Relevant DNELs of components						
Name of substance	CAS No	Endpoint	Threshold level	Protection goal, route of exposure	Used in	Exposure time
N-methyl-N-[C18-(unsaturated)alkanoyl]glycine		DNEL	0.8 mg/m ³	human, inhalatory	worker (industry)	chronic - systemic effects
N-methyl-N-[C18-(unsaturated)alkanoyl]glycine		DNEL	4.2 mg/kg bw/day	human, dermal	worker (industry)	chronic - systemic effects
Sulfonic acids, petroleum, calcium salts	61789-86-4	DNEL	11.75 mg/m ³	human, inhalatory	worker (industry)	chronic - systemic effects
Sulfonic acids, petroleum, calcium salts	61789-86-4	DNEL	3.33 mg/kg bw/day	human, dermal	worker (industry)	chronic - systemic effects

Relevant PNECs of components						
Name of substance	CAS No	Endpoint	Threshold level	Organism	Environmental compartment	Exposure time
N-methyl-N-[C18-(unsaturated)alkanoyl]glycine		PNEC	0.004 mg/l	aquatic organisms	freshwater	short-term (single instance)
N-methyl-N-[C18-(unsaturated)alkanoyl]glycine		PNEC	0 mg/l	aquatic organisms	marine water	short-term (single instance)
N-methyl-N-[C18-(unsaturated)alkanoyl]glycine		PNEC	1 mg/l	aquatic organisms	sewage treatment plant (STP)	short-term (single instance)
N-methyl-N-[C18-(unsaturated)alkanoyl]glycine		PNEC	0.057 mg/kg	aquatic organisms	freshwater sediment	short-term (single instance)
N-methyl-N-[C18-(unsaturated)alkanoyl]glycine		PNEC	0.006 mg/kg	aquatic organisms	marine sediment	short-term (single instance)
N-methyl-N-[C18-(unsaturated)alkanoyl]glycine		PNEC	1.71 mg/kg	terrestrial organisms	soil	short-term (single instance)
Sulfonic acids, petroleum, calcium salts	61789-86-4	PNEC	1 mg/l	aquatic organisms	freshwater	short-term (single instance)
Sulfonic acids, petroleum, calcium salts	61789-86-4	PNEC	1 mg/l	aquatic organisms	marine water	short-term (single instance)
Sulfonic acids, petroleum, calcium salts	61789-86-4	PNEC	1,000 mg/l	aquatic organisms	sewage treatment plant (STP)	short-term (single instance)
Sulfonic acids, petroleum, calcium salts	61789-86-4	PNEC	226,000,000 mg/kg	aquatic organisms	freshwater sediment	short-term (single instance)
Sulfonic acids, petroleum, calcium salts	61789-86-4	PNEC	226,000,000 mg/kg	aquatic organisms	marine sediment	short-term (single instance)
Sulfonic acids, petroleum, calcium salts	61789-86-4	PNEC	271,000,000 mg/kg	terrestrial organisms	soil	short-term (single instance)

8.2 Exposure controls

Interflon Lube EPR

Version number: 1.1

date of issue
2026-04-15

Date of compilation: Revi-
sion: 2026-04-15

General safety precautions

Use only in well-ventilated areas.
In case of insufficient ventilation, wear suitable respiratory equipment.
Avoid contact with skin and eyes.
Keep away from food, drink and animal feedingstuffs. Do not breathe gas/vapour/spray. Wash hands after use.

Individual protection measures (personal protective equipment)

Eye/face protection

Work with safety glasses.

Skin protection

- Hand protection

Chemical protection gloves are suitable, which are tested according to EN 374. When handling with chemical substances, protective gloves must be worn with the CE-label including the four control digits. Type of material. NBR: acrylonitrile-butadiene rubber. CR: chloroprene (chlorobutadiene) rubber. PVC: polyvinyl chloride.

- Other protection measures

Take recovery periods for skin regeneration. Preventive skin protection (barrier creams/ointments) is recommended. Wash hands thoroughly after handling.

Respiratory protection

[In case of inadequate ventilation] wear respiratory protection. Type: A-P2 (combined filters against particles and organic gases and vapours, colour code: Brown/White).

Environmental exposure controls

Use appropriate container to avoid environmental contamination. Keep away from drains, surface and ground water.

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

Physical state	liquid
Colour	beige
Odour	characteristic
Melting point/freezing point	not determined
Boiling point or initial boiling point and boiling range	186 °C at 1 atm
Flammability	non-combustible
Lower and upper explosion limit	0.6 vol% - 7 vol% non-combustible
Flash point	65 °C at 1 atm not relevant
Auto-ignition temperature	>200 °C (auto-ignition temperature (liquids and gases))
Decomposition temperature	not relevant
pH (value)	not determined
Kinematic viscosity	27 cSt at 40 °C not relevant
Solubility(ies)	easily soluble

Partition coefficient

Partition coefficient n-octanol/water (log value)	not relevant
---	--------------

Interflon Lube EPR

Version number: 1.1

 date of issue
2026-04-15

 Date of compilation: Revi-
sion: 2026-04-15

Vapour pressure	0.05 kPa at 20 °C
-----------------	-------------------

Density and/or relative density

Density	0.85 g/cm ³ at 20 °C
Relative vapour density	information on this property is not available / not relevant

Particle characteristics	not relevant (liquid)
--------------------------	-----------------------

9.2 Other information

Information with regard to physical hazard classes	hazard classes acc. to GHS (physical hazards): not relevant
Other safety characteristics	there is no additional information

SECTION 10: Stability and reactivity

10.1 Reactivity

Concerning incompatibility: see below "Conditions to avoid" and "Incompatible materials".

10.2 Chemical stability

See below "Conditions to avoid".

10.3 Possibility of hazardous reactions

No known hazardous reactions.

10.4 Conditions to avoid

There are no specific conditions known which have to be avoided.

10.5 Incompatible materials

Oxidisers

10.6 Hazardous decomposition products

Hazardous combustion products: see section 5.

SECTION 11: Toxicological information

11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

Test data are not available for the complete mixture.

Classification procedure

The method for classification of the mixture is based on ingredients of the mixture (additivity formula).

Classification according to GHS (1272/2008/EC, CLP)

Acute toxicity

Shall not be classified as acutely toxic.

Acute toxicity estimate (ATE) of components			
Name of substance	CAS No	Exposure route	ATE
N-methyl-N-[C18-(unsaturated)alkanoyl]glycine		inhalation: vapour	11 mg/l/4h
N-methyl-N-[C18-(unsaturated)alkanoyl]glycine		inhalation: dust/mist	1.37

Interflon Lube EPR

Version number: 1.1

date of issue
2026-04-15

Date of compilation: Revision:
2026-04-15

Acute toxicity estimate (ATE) of components			
Name of substance	CAS No	Exposure route	ATE
			mg/l/4h

Acute toxicity of components					
Name of substance	CAS No	Exposure route	Endpoint	Value	Species
N-methyl-N-[C18-(unsaturated)alkanoyl]glycine		oral	LD50	>5,000 mg/kg	rat
N-methyl-N-[C18-(unsaturated)alkanoyl]glycine		inhalation: dust/mist	LC50	1.37 mg/l/4h	rat

Skin corrosion/irritation

Shall not be classified as corrosive/irritant to skin.

Serious eye damage/eye irritation

Causes serious eye irritation.

Respiratory or skin sensitisation

Contains Sulfonic acids, petroleum, calcium salts. May produce an allergic reaction.

Germ cell mutagenicity

Shall not be classified as germ cell mutagenic.

Carcinogenicity

Shall not be classified as carcinogenic.

Reproductive toxicity

Shall not be classified as a reproductive toxicant.

Specific target organ toxicity - single exposure

Shall not be classified as a specific target organ toxicant (single exposure).

Specific target organ toxicity - repeated exposure

Shall not be classified as a specific target organ toxicant (repeated exposure).

Aspiration hazard

Shall not be classified as presenting an aspiration hazard.

Other information

Repeated exposure may cause skin dryness or cracking.

11.2 Information on other hazards

There is no additional information.

SECTION 12: Ecological information

12.1 Toxicity

Shall not be classified as hazardous to the aquatic environment.

12.2 Persistence and degradability

Data are not available.

12.3 Bioaccumulative potential

Data are not available.

12.4 Mobility in soil

Data are not available.

12.5 Results of PBT and vPvB assessment

This mixture does not contain any substances that are assessed to be a PBT or a vPvB.

Interflon Lube EPR

Version number: 1.1

date of issue
2026-04-15Date of compilation: Revi-
sion: 2026-04-15

12.6 Endocrine disrupting properties

Does not contain an endocrine disruptor (ED) at a concentration of $\geq 0,1\%$.

12.7 Other adverse effects

Data are not available.

SECTION 13: Disposal considerations

13.1 Waste treatment methods

Sewage disposal-relevant information

Do not empty into drains.

Waste treatment of containers/packages

This article should be disposed of as hazardous waste. Please do not put it in your normal household waste. Dispose of this material and its container to hazardous or special waste collection point. Handle contaminated packages in the same way as the substance itself.

Relevant provisions relating to waste

Properties of waste which render it hazardous

HP 14 ecotoxic

List of wastes

- Product
13 02 07* readily biodegradable engine, gear and lubricating oils

Remarks

Please consider the relevant national or regional provisions. Waste shall be separated into the categories that can be handled separately by the local or national waste management facilities.

SECTION 14: Transport information

14.1 UN number or ID number	not subject to transport regulations
14.2 UN proper shipping name	not relevant
14.3 Transport hazard class(es)	none
14.4 Packing group	not assigned
14.5 Environmental hazards	non-environmentally hazardous acc. to the dangerous goods regulations
14.6 Special precautions for user	There is no additional information.
14.7 Maritime transport in bulk according to IMO instruments	The cargo is not intended to be carried in bulk.

Information for each of the UN Model Regulations

International Maritime Dangerous Goods Code (IMDG) - Additional information

Not subject to IMDG.

International Civil Aviation Organization (ICAO-IATA/DGR) - Additional information

Not subject to ICAO-IATA.

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture Relevant provisions of the European Union (EU)

Interflon Lube EPR

Version number: 1.1

 date of issue
2026-04-15

 Date of compilation: Revi-
sion: 2026-04-15

Restrictions according to REACH, Annex XVII

Dangerous substances with restrictions (REACH, Annex XVII)				
Name of substance	Name acc. to inventory	CAS No	Restriction	No
Interflon Lube EPR	this product meets the criteria for classification in accordance with Regulation No 1272/2008/EC		R3	3
N-methyl-N-[C18-(unsaturated)alkanoyl]glycine	substances in tattoo inks and permanent make-up		R75	75

Legend

- R3**
- Shall not be used in:
 - ornamental articles intended to produce light or colour effects by means of different phases, for example in ornamental lamps and ashtrays,
 - tricks and jokes,
 - games for one or more participants, or any article intended to be used as such, even with ornamental aspects,
 - Articles not complying with paragraph 1 shall not be placed on the market.
 - Shall not be placed on the market if they contain a colouring agent, unless required for fiscal reasons, or perfume, or both, if they:
 - can be used as fuel in decorative oil lamps for supply to the general public, and
 - present an aspiration hazard and are labelled with H304.
 - Decorative oil lamps for supply to the general public shall not be placed on the market unless they conform to the European Standard on Decorative oil lamps (EN 14059) adopted by the European Committee for Standardisation (CEN).
 - Without prejudice to the implementation of other Union provisions relating to the classification, labelling and packaging of substances and mixtures, suppliers shall ensure, before the placing on the market, that the following requirements are met:
 - lamp oils, labelled with H304, intended for supply to the general public are visibly, legibly and indelibly marked as follows: "Keep lamps filled with this liquid out of the reach of children"; and, by 1 December 2010, "Just a sip of lamp oil – or even sucking the wick of lamps – may lead to life-threatening lung damage";
 - grill lighter fluids, labelled with H304, intended for supply to the general public are legibly and indelibly marked by 1 December 2010 as follows: "Just a sip of grill lighter fluid may lead to life threatening lung damage";
 - lamps oils and grill lighters, labelled with H304, intended for supply to the general public are packaged in black opaque containers not exceeding 1 litre by 1 December 2010.;
- R75**
- Shall not be placed on the market in mixtures for use for tattooing purposes, and mixtures containing any such substances shall not be used for tattooing purposes, after 4 January 2022 if the substance or substances in question is or are present in the following circumstances:
 - in the case of a substance classified in Part 3 of Annex VI to Regulation (EC) No 1272/2008 as carcinogen category 1A, 1B or 2, or germ cell mutagen category 1A, 1B or 2, the substance is present in the mixture in a concentration equal to or greater than 0,00005 % by weight;
 - in the case of a substance classified in Part 3 of Annex VI to Regulation (EC) No 1272/2008 as reproductive toxicant category 1A, 1B or 2, the substance is present in the mixture in a concentration equal to or greater than 0,001 % by weight;
 - in the case of a substance classified in Part 3 of Annex VI to Regulation (EC) No 1272/2008 as skin sensitizer category 1, 1A or 1B, the substance is present in the mixture in a concentration equal to or greater than 0,001 % by weight;
 - in the case of a substance classified in Part 3 of Annex VI to Regulation (EC) No 1272/2008 as skin corrosive category 1, 1A, 1B or 1C or skin irritant category 2, or as serious eye damage category 1 or eye irritant category 2, the substance is present in the mixture in a concentration equal to or greater than:
 - 0,1 % by weight, if the substance is used solely as a pH regulator;
 - 0,01 % by weight, in all other cases;
 - in the case of a substance listed in Annex II to Regulation (EC) No 1223/2009 (*1), the substance is present in the mixture in a concentration equal to or greater than 0,00005 % by weight;
 - in the case of a substance for which a condition of one or more of the following kinds is specified in column g (Product type, Body parts) of the table in Annex IV to Regulation (EC) No 1223/2009, the substance is present in the mixture in a concentration equal to or greater than 0,00005 % by weight:
 - "Rinse-off products";
 - "Not to be used in products applied on mucous membranes";
 - "Not to be used in eye products";
 - in the case of a substance for which a condition is specified in column h (Maximum concentration in ready for use preparation) or column i (Other) of the table in Annex IV to Regulation (EC) No 1223/2009, the substance is present in the mixture in a concentration, or in some other way, that does not accord with the condition specified in that column;
 - in the case of a substance listed in Appendix 13 to this Annex, the substance is present in the mixture in a concentration equal to or greater than the concentration limit specified for that substance in that Appendix.
 - For the purposes of this entry use of a mixture "for tattooing purposes" means injection or introduction of the mixture into a person's skin, mucous membrane or eyeball, by any process or procedure (including procedures commonly referred to as permanent make-up, cosmetic tattooing, micro-blading and micro-pigmentation), with the aim of making a mark or design on his or her body.
 - If a substance not listed in Appendix 13 falls within more than one of points (a) to (g) of paragraph 1, the strictest concentration limit laid down in the points in question shall apply to that substance. If a substance listed in Appendix 13 also falls within one or more of points (a) to (g) of paragraph 1, the concentration limit laid down in point (h) of paragraph 1 shall apply to that substance.
 - By way of derogation, paragraph 1 shall not apply to the following substances until 4 January 2023:
 - Pigment Blue 15:3 (CI 74160, EC No 205-685-1, CAS No 147-14-8);
 - Pigment Green 7 (CI 74260, EC No 215-524-7, CAS No 1328-53-6).
 - If Part 3 of Annex VI to Regulation (EC) No 1272/2008 is amended after 4 January 2021 to classify or re-classify a substance such that the substance then becomes caught by point (a), (b), (c) or (d) of paragraph 1 of this entry, or such that it then falls

Interflon Lube EPR

Version number: 1.1

date of issue
2026-04-15

Date of compilation: Revi-
sion: 2026-04-15

Legend

within a different one of those points from the one within which it fell previously, and the date of application of that new or revised classification is after the date referred to in paragraph 1 or, as the case may be, paragraph 4 of this entry, that amendment shall, for the purposes of applying this entry to that substance, be treated as taking effect on the date of application of that new or revised classification.

6. If Annex II or Annex IV to Regulation (EC) No 1223/2009 is amended after 4 January 2021 to list or change the listing of a substance such that the substance then becomes caught by point (e), (f) or (g) of paragraph 1 of this entry, or such that it then falls within a different one of those points from the one within which it fell previously, and the amendment takes effect after the date referred to in paragraph 1 or, as the case may be, paragraph 4 of this entry, that amendment shall, for the purposes of applying this entry to that substance, be treated as taking effect from the date falling 18 months after entry into force of the act by which that amendment was made.

7. Suppliers placing a mixture on the market for use for tattooing purposes shall ensure that, after 4 January 2022, the mixture is marked with the following information:

(a) the statement "Mixture for use in tattoos or permanent make-up";

(b) a reference number to uniquely identify the batch;

(c) the list of ingredients in accordance with the nomenclature established in the glossary of common ingredient names pursuant to Article 33 of Regulation (EC) No 1223/2009, or in the absence of a common ingredient name, the IUPAC name. In the absence of a common ingredient name or IUPAC name, the CAS and EC number. Ingredients shall be listed in descending order by weight or volume of the ingredients at the time of formulation. "Ingredient" means any substance added during the process of formulation and present in the mixture for use for tattooing purposes. Impurities shall not be regarded as ingredients. If the name of a substance, used as ingredient within the meaning of this entry, is already required to be stated on the label in accordance with Regulation (EC) No 1272/2008, that ingredient does not need to be marked in accordance with this Regulation;

(d) the additional statement "pH regulator" for substances falling under point (d)(i) of paragraph 1;

(e) the statement "Contains nickel. Can cause allergic reactions." if the mixture contains nickel below the concentration limit specified in Appendix 13;

(f) the statement "Contains chromium (VI). Can cause allergic reactions." if the mixture contains chromium (VI) below the concentration limit specified in Appendix 13;

(g) safety instructions for use insofar as they are not already required to be stated on the label by Regulation (EC) No 1272/2008.

The information shall be clearly visible, easily legible and marked in a way that is indelible.

The information shall be written in the official language(s) of the Member State(s) where the mixture is placed on the market, unless the Member State(s) concerned provide(s) otherwise.

Where necessary because of the size of the package, the information listed in the first subparagraph, except for point (a), shall be included instead in the instructions for use.

Before using a mixture for tattooing purposes, the person using the mixture shall provide the person undergoing the procedure with the information marked on the package or included in the instructions for use pursuant to this paragraph.

8. Mixtures that do not contain the statement "Mixture for use in tattoos or permanent make-up" shall not be used for tattooing purposes.

9. This entry does not apply to substances that are gases at temperature of 20 °C and pressure of 101,3 kPa, or generate a vapour pressure of more than 300 kPa at temperature of 50 °C, with the exception of formaldehyde (CAS No 50-00-0, EC No 200-001-8).

10. This entry does not apply to the placing on the market of a mixture for use for tattooing purposes, or to the use of a mixture for tattooing purposes, when placed on the market exclusively as a medical device or an accessory to a medical device, within the meaning of Regulation (EU) 2017/745, or when used exclusively as a medical device or an accessory to a medical device, within the same meaning. Where the placing on the market or use may not be exclusively as a medical device or an accessory to a medical device, the requirements of Regulation (EU) 2017/745 and of this Regulation shall apply cumulatively.

List of substances subject to authorisation (REACH, Annex XIV) / SVHC - candidate list

not relevant

Seveso Directive

2012/18/EU (Seveso III)			
No	Dangerous substance/hazard categories	Qualifying quantity (tonnes) for the application of lower and upper-tier requirements	Notes
	not assigned		

Industrial Emissions Directive (IED)

VOC content	47.32 %
-------------	---------

Directive on the restriction of the use of certain hazardous substances in electrical and electronic equipment (RoHS)

none of the ingredients are listed

Regulation concerning the establishment of a European Pollutant Release and Transfer Register (PRTR)

none of the ingredients are listed

Regulation on persistent organic pollutants (POP)

Interflon Lube EPR

Version number: 1.1

 date of issue
2026-04-15

 Date of compilation: Revi-
sion: 2026-04-15

none of the ingredients are listed

National inventories

Country	Inventory	Status
CA	DSL	not all ingredients are listed
EU	REACH Reg.	all ingredients are listed or exempt from listing
US	TSCA	not all ingredients are listed

Legend

DSL Domestic Substances List (DSL)
 REACH Reg. REACH registered substances
 TSCA Toxic Substance Control Act

15.2 Chemical safety assessment

Chemical safety assessments for substances in this mixture were not carried out.

SECTION 16: Other information

Indication of changes (revised safety data sheet)

Section	Former entry (text/value)	Actual entry (text/value)	Safety-relevant
1.1	Unique formula identifier UFI: 9E50-F0WY-1006-CPH7	Unique formula identifier UFI: JH50-Y0MC-A00Q-0139	yes

Abbreviations and acronyms

Abbr.	Descriptions of used abbreviations
Acute Tox.	Acute toxicity
ADR	Accord relatif au transport international des marchandises dangereuses par route (Agreement concerning the International Carriage of Dangerous Goods by Road)
Aquatic Acute	Hazardous to the aquatic environment - acute hazard
Aquatic Chronic	Hazardous to the aquatic environment - chronic hazard
Asp. Tox.	Aspiration hazard
ATE	Acute Toxicity Estimate
CAS	Chemical Abstracts Service (service that maintains the most comprehensive list of chemical substances)
CLP	Regulation (EC) No 1272/2008 on classification, labelling and packaging of substances and mixtures
DGR	Dangerous Goods Regulations (see IATA/DGR)
DNEL	Derived No-Effect Level
EC No	The EC Inventory (EINECS, ELINCS and the NLP-list) is the source for the seven-digit EC number, an identifier of substances commercially available within the EU (European Union)
ED	Endocrine disruptor
EINECS	European Inventory of Existing Commercial Chemical Substances
ELINCS	European List of Notified Chemical Substances
Eye Dam.	Seriously damaging to the eye
Eye Irrit.	Irritant to the eye
GHS	"Globally Harmonized System of Classification and Labelling of Chemicals" developed by the United Nations
IATA	International Air Transport Association

Interflon Lube EPR

Version number: 1.1

 date of issue
2026-04-15

 Date of compilation: Revi-
sion: 2026-04-15

Abbr.	Descriptions of used abbreviations
IATA/DGR	Dangerous Goods Regulations (DGR) for the air transport (IATA)
ICAO	International Civil Aviation Organization
IMDG	International Maritime Dangerous Goods Code
index No	The Index number is the identification code given to the substance in Part 3 of Annex VI to Regulation (EC) No 1272/2008
LC50	Lethal Concentration 50%: the LC50 corresponds to the concentration of a tested substance causing 50 % lethality during a specified time interval
LD50	Lethal Dose 50 %: the LD50 corresponds to the dose of a tested substance causing 50 % lethality during a specified time interval
M-factor	Means a multiplying factor. It is applied to the concentration of a substance classified as hazardous to the aquatic environment acute category 1 or chronic category 1, and is used to derive by the summation method the classification of a mixture in which the substance is present
NLP	No-Longer Polymer
PBT	Persistent, Bioaccumulative and Toxic
PNEC	Predicted No-Effect Concentration
REACH	Registration, Evaluation, Authorisation and Restriction of Chemicals
RID	Règlement concernant le transport International ferroviaire des marchandises Dangereuses (Regulations concerning the International carriage of Dangerous goods by Rail)
Skin Corr.	Corrosive to skin
Skin Irrit.	Irritant to skin
Skin Sens.	Skin sensitisation
SVHC	Substance of Very High Concern
UFI	Unique formula identifier
VOC	Volatile Organic Compounds
vPvB	Very Persistent and very Bioaccumulative

Key literature references and sources for data

Regulation (EC) No 1272/2008 on classification, labelling and packaging of substances and mixtures. Regulation (EC) No. 1907/2006 (REACH), amended by 2020/878/EU.

Agreement concerning the International Carriage of Dangerous Goods by Road (ADR). Regulations concerning the International Carriage of Dangerous Goods by Rail (RID). International Maritime Dangerous Goods Code (IMDG). Dangerous Goods Regulations (DGR) for the air transport (IATA).

Classification procedure

Physical and chemical properties: The classification is based on tested mixture.

Health hazards, Environmental hazards: The method for classification of the mixture is based on ingredients of the mixture (additivity formula).

List of relevant phrases (code and full text as stated in section 2 and 3)

Code	Text
H304	May be fatal if swallowed and enters airways.
H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H318	Causes serious eye damage.
H319	Causes serious eye irritation.
H332	Harmful if inhaled.

Interflon Lube EPR

Version number: 1.1

date of issue
2026-04-15

Date of compilation: Revi-
sion: 2026-04-15

Code	Text
H400	Very toxic to aquatic life.
H412	Harmful to aquatic life with long lasting effects.

Disclaimer

This information is based upon the present state of our knowledge. This SDS has been compiled and is solely intended for this product.