

acc. to Safe Work Australia's Code of Practice for Labelling of Workplace Hazardous Chemicals (under WHS Regulations)

Interflon Lube EP+ (Aerosol)

Date of issue **Version number: Revision:** 2025-04-02 2025-04-02. 6.5

Replaces version: 5:

SECTION 1: Identification of the substance/mixture and of the company/undertaking

Product identifier 1.1

Trade name **Interflon Lube EP+ (Aerosol)**

1.2 Relevant identified uses of the substance or mixture and uses advised against

lubricant

1.3 Details of the supplier of the safety data sheet

Interflon BV Belder 47 4704 RK Roosendaal Netherlands

Telephone: +31 (0)165 553911 e-mail: Service@Interflon.com Website: www.Interflon.com

Supplier (importer) Interflon Australia 13 Sigvard Blvd Hallam VIC 3803 Telephone: +61 402 522 112 Melvelle Equipment Australia +61 2 4951 5244

+61 2 4950 1291

Andrew@melvelle.com.au e-mail (competent person)

australia@interflon.com

1.4 **Emergency telephone number**

Poison centre					
	Name	Street	City	Telephone	
Ī	Queensland Poisons Information Centre		South Brisbane	131126	

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Classification acc. to GHS

Section	Hazard class	Category	Hazard class and cat- egory	Hazard state- ment
2.3	aerosols	1	Aerosol 1	H222,H229
3.2	skin corrosion/irritation	2	Skin Irrit. 2	H315
3.3	serious eye damage/eye irritation	2	Eye Irrit. 2	H319
3.8D	specific target organ toxicity - single exposure (narcotic effects, drowsiness)	3	STOT SE 3	H336

For full text of abbreviations: see SECTION 16.

Australia: en Page: 1 / 14



acc. to Safe Work Australia's Code of Practice for Labelling of Workplace

Hazardous Chemicals (under WHS Regulations)

Interflon Lube EP+ (Aerosol)

Version number: 6.5 date of issue Revision: 2025-04-02 Replaces version of: (5) 2025-04-02

2.2 Label elements

Labelling

- Signal word. danger

- Pictograms

GHS02, GHS07



- Hazard statements

H222 Extremely flammable aerosol.

H229 Pressurised container: may burst if heated.

H315 Causes skin irritation.
 H319 Causes serious eye irritation.
 H336 May cause drowsiness or dizziness.

- Precautionary statements

P210 Keep away from heat/sparks/open flames/hot surfaces. - No smoking.

P211 Do not spray on an open flame or other ignition source.
P251 Pressurized container: Do not pierce or burn, even after use.
P261 Avoid breathing dust/fume/gas/mist/vapours/spray.

P280 Wear protective gloves.

P312 Call a POISON CENTER or doctor/physician if you feel unwell.
P403+P233 Store in a well-ventilated place. Keep container tightly closed.

P410+P412 Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F.

P501 Dispose of contents/container to industrial combustion plant.

- Hazardous ingredients for labelling

Hydrocarbons, C7, n-alkanes, isoalkanes, cyclics, Hydrocarbons, C6, isoalkanes, <5% n-hexane

2.3 Other hazards

This mixture does not contain any substances that are assessed to be a PBT or a vPvB.

Results of PBT and vPvB assessment

Does not contain a PBT-/vPvB-substance at a concentration of \geq 0,1%.

Endocrine disrupting properties

Does not contain an endocrine disruptor (ED) at a concentration of \geq 0,1%.

SECTION 3: Composition/information on ingredients

3.1 Substances

Not relevant (mixture)

3.2 Mixtures

Product description

Mixture of mineral and vegetable oils, additives and $\mbox{Micpol} \ensuremath{\mathbb{R}}$

Hazardous ingredients

Name of substance	Identifier	Wt%	Classification acc. to GHS	Notes
butane	CAS No 106-97-8	10 - < 25	Flam. Gas 1 / H220 Press. Gas C / H280	C(a) U
Propane	CAS No 74-98-6	10 - < 25	Flam. Gas 1 / H220 Press. Gas C / H280	
Hydrocarbons, C10-C13, n-al- kanes, isoalkanes, cyclics, <	CAS No 64742-48-9	7.5 - < 10	Flam. Liq. 4 / H227 Asp. Tox. 1 / H304	L(b)

Australia: en Page: 2 / 14



acc. to Safe Work Australia's Code of Practice for Labelling of Workplace $\,$

Hazardous Chemicals (under WHS Regulations)

Interflon Lube EP+ (Aerosol)

Version number: 6.5date of issueRevision: 2025-04-02Replaces version of: (5)2025-04-02

Name of substance	Identifier	Wt%	Classification acc. to GHS	Notes
2% aromatics				
Hydrocarbons, C7, n-alkanes, isoalkanes, cyclics	CAS No 64742-49-0	7.5 - < 10	Flam. Liq. 2 / H225 Skin Irrit. 2 / H315 STOT SE 3 / H336 Asp. Tox. 1 / H304	
Hydrocarbons, C6, isoalkanes, <5% n-hexane	CAS No 64742-49-0	5 - < 7.5	Flam. Liq. 2 / H225 Skin Irrit. 2 / H315 STOT SE 3 / H336 Asp. Tox. 1 / H304	
(Z)-N-methyl-N-(1-oxo-9-octa- decenyl)glycine	CAS No 110-25-8	1 - < 2.5	Acute Tox. 4 / H332 Skin Irrit. 2 / H315 Eye Dam. 1 / H318	

Notes

C(a): Mixture of isomers

L(b): The classification as a carcinogen is not required. The substance contains less than 3 % DMSO extract

U: When put on the market gases have to be classified as 'Gases under pressure', in one of the groups compressed gas, lique-fied gas, refrigerated liquefied gas or dissolved gas. The group depends on the physical state in which the gas is packaged and therefore has to be assigned case by case.

Regulation 648/2004/EC on detergents

Wt%	Constituents	Weight % content (or range)
≥30%	aliphatic hydrocarbons	30 % and more

Remarks

For full text of Hazard- and EU Hazard-statements: see SECTION 16.

SECTION 4: First aid measures

4.1 Description of first aid measures

General notes

Do not leave affected person unattended. Remove victim out of the danger area. Keep affected person warm, still and covered. Take off immediately all contaminated clothing. In all cases of doubt, or when symptoms persist, seek medical advice. In case of unconsciousness place person in the recovery position. Never give anything by mouth.

Following inhalation

If breathing is irregular or stopped, immediately seek medical assistance and start first aid actions. In case of respiratory tract irritation, consult a physician. Provide fresh air.

Following skin contact

Wash with plenty of soap and water.

Following eye contact

Remove contact lenses, if present and easy to do. Continue rinsing. Irrigate copiously with clean, fresh water for at least 10 minutes, holding the eyelids apart.

Following ingestion

Rinse mouth with water (only if the person is conscious). Do NOT induce vomiting.

4.2 Most important symptoms and effects, both acute and delayed

Symptoms and effects are not known to date.

4.3 Indication of any immediate medical attention and special treatment needed

none

Australia: en Page: 3 / 14



acc. to Safe Work Australia's Code of Practice for Labelling of Workplace

Hazardous Chemicals (under WHS Regulations)

Interflon Lube EP+ (Aerosol)

Version number: 6.5date of issueRevision: 2025-04-02Replaces version of: (5)2025-04-02

SECTION 5: Firefighting measures

5.1 Extinguishing media

Suitable extinguishing media

Water spray, Water mist, Fire extinguishing powder, Carbon dioxide (CO2), Alcohol resistant foam

Unsuitable extinguishing media

Water jet

5.2 Special hazards arising from the substance or mixture

In case of insufficient ventilation and/or in use, may form flammable/explosive vapour-air mixture.

Hazardous combustion products

Nitrogen oxides (NOx), Carbon monoxide (CO), Carbon dioxide (CO2)

5.3 Advice for firefighters

In case of fire and/or explosion do not breathe fumes. Co-ordinate firefighting measures to the fire surroundings. Do not allow firefighting water to enter drains or water courses. Collect contaminated firefighting water separately. Fight fire with normal precautions from a reasonable distance. Use suitable breathing apparatus.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

For non-emergency personnel

Remove persons to safety.

For emergency responders

Wear breathing apparatus if exposed to vapours/dust/spray/gases.

6.2 Environmental precautions

Keep away from drains, surface and ground water. Retain contaminated washing water and dispose of it.

6.3 Methods and material for containment and cleaning up

Advice on how to contain a spill

Covering of drains

Other information relating to spills and releases

Place in appropriate containers for disposal. Ventilate affected area.

6.4 Reference to other sections

Hazardous combustion products: see section 5. Personal protective equipment: see section 8. Incompatible materials: see section 10. Disposal considerations: see section 13.

SECTION 7: Handling and storage

7.1 Precautions for safe handling

Recommendations

- Measures to prevent fire as well as aerosol and dust generation

Use local and general ventilation. Take precautionary measures against static discharge. Use only in well-ventilated areas. Ground/bond container and receiving equipment.

Advice on general occupational hygiene

Remove contaminated clothing and protective equipment before entering eating areas. Never place chemicals in containers that are normally used for food or drink.

7.2 Conditions for safe storage, including any incompatibilities

Conditions of storage

Store in accordance with local/regional/national/international regulations. Keep container tightly closed and in a well-ventilated place.

Australia: en Page: 4 / 14



acc. to Safe Work Australia's Code of Practice for Labelling of Workplace
Hazardous Chemicals (under WHS Regulations)

Interflon Lube EP+ (Aerosol)

Version number: 6.5date of issueRevision: 2025-04-02Replaces version of: (5)2025-04-02

Managing of associated risks

- Flammability hazards

Do not spray on an open flame or other ignition source. Protect from sunlight. Keep in a cool place.

- Packaging compatibilities

Only packagings which are approved (e.g. acc. to the Dangerous Goods Regulations) may be used.

7.3 Specific end use(s)

See section 16 for a general overview.

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Occupational exposure limit values (Workplace Exposure Limits)

Occupational exposure limit values (Workplace Exposure Limits)										
Coun- try	Name of agent	CAS No	Identi- fier	TWA [ppm]	TWA [mg/m³]	STEL [ppm]	STEL [mg/m³]	Ceiling-C [mg/m³]	Nota- tion	Source
AU	butane	106-97-8	WES	800	1,900					WES
AU	white spirit (min- eral turpentine)	64742-48-9	WES		480					WES

Notation

Ceiling-C ceiling value is a limit value above which exposure should not occur

STEL short-term exposure limit: a limit value above which exposure should not occur and which is related to a 15-minute peri-

od (unless otherwise specified)

TWA time-weighted average (long-term exposure limit): measured or calculated in relation to a reference period of 8 hours

time-weighted average (unless otherwise specified)

Relevant DNELs o	f componen					
Name of substance	CAS No	Endpoint	Threshold level	Protection goal, route of exposure	Used in	Exposure time
Hydrocarbons, C7, n- alkanes, isoalkanes, cyclics	64742-49-0	DNEL	2,085 mg/m ³	human, inhalatory	worker (industry)	chronic - systemic effects
Hydrocarbons, C7, n- alkanes, isoalkanes, cyclics	64742-49-0	DNEL	300 mg/kg bw/day	human, dermal	worker (industry)	chronic - systemic effects
Hydrocarbons, C6, isoalkanes, <5% n- hexane	64742-49-0	DNEL	5,306 mg/m ³	human, inhalatory	worker (industry)	chronic - systemic effects
Hydrocarbons, C6, isoalkanes, <5% n- hexane	64742-49-0	DNEL	13,964 mg/kg bw/day	human, dermal	worker (industry)	chronic - systemic effects

8.2 Exposure controls

General safety precautions

Use only in well-ventilated areas.

In case of insufficient ventilation, wear suitable respiratory equipment.

Avoid contact with skin and eyes.

Keep away from food, drink and animal feedingstuffs. Do not breathe gas/vapour/spray. Wash hands after use.

Individual protection measures (personal protective equipment)

Eye/face protection

Work with safety glasses.

Australia: en Page: 5 / 14



acc. to Safe Work Australia's Code of Practice for Labelling of Workplace
Hazardous Chemicals (under WHS Regulations)

Interflon Lube EP+ (Aerosol)

Version number: 6.5date of issueRevision: 2025-04-02Replaces version of: (5)2025-04-02

Skin protection

- Hand protection

When handling with chemical substances, protective gloves must be worn with the CE-label including the four control digits. Type of material. NBR: acrylonitrile-butadiene rubber. CR: chloroprene (chlorobutadiene) rubber. PVC: polyvinyl chloride.

- Other protection measures

Take recovery periods for skin regeneration. Preventive skin protection (barrier creams/ointments) is recommended. Wash hands thoroughly after handling.

Respiratory protection

[In case of inadequate ventilation] wear respiratory protection. Type: A-P2 (combined filters against particles and organic gases and vapours, colour code: Brown/White).

Environmental exposure controls

Use appropriate container to avoid environmental contamination. Keep away from drains, surface and ground water.

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

Physical state	liquid, gaseous (spray aerosol)
Colour	brown
Odour	Like oil
Melting point/freezing point	not determined
Boiling point or initial boiling point and boiling range	<0 °C at 1,013 hPa
Flammability	flammable aerosol in accordance with GHS criteria
Lower and upper explosion limit	0.6 vol% - 10 vol%
Flash point	<-60 °C at 1,013 hPa
Auto-ignition temperature	>200 °C (auto-ignition temperature (liquids and gases))
Decomposition temperature	not relevant
pH (value)	not relevant
Kinematic viscosity	not determined
Solubility(ies)	not determined

Partition coefficient

Partition coefficient n-octanol/water (log value)	this information is not available
Vapour pressure	4,200 hPa at 20 °C

Australia: en Page: 6 / 14



acc. to Safe Work Australia's Code of Practice for Labelling of Workplace
Hazardous Chemicals (under WHS Regulations)

Interflon Lube EP+ (Aerosol)

Version number: 6.5date of issueRevision: 2025-04-02Replaces version of: (5)2025-04-02

Density and/or relative density

Density	0.72 ^g / _{cm³} at 20 °C
Relative vapour density	information on this property is not available

Particle characteristics	not relevant (aerosol)
ר מו נוכופ כוומו מכנפו ואנוכא	HOUTEIEVAITE (aerosoi)

9.2 Other information

Information with regard to physical hazard classes

Aerosols

- Components (flammable)	44 % 44 % by mass of the contents are flammable
Other safety characteristics	there is no additional information

SECTION 10: Stability and reactivity

10.1 Reactivity

Concerning incompatibility: see below "Conditions to avoid" and "Incompatible materials". The mixture contains reactive substance(s). Risk of ignition.

10.2 Chemical stability

See below "Conditions to avoid".

10.3 Possibility of hazardous reactions

No known hazardous reactions.

10.4 Conditions to avoid

Do not spray on an open flame or other ignition source. Keep away from heat.

Hints to prevent fire or explosion

Protect from sunlight.

10.5 Incompatible materials

Oxidisers

10.6 Hazardous decomposition products

Hazardous combustion products: see section 5.

SECTION 11: Toxicological information

11.1 Information on toxicological effects

Test data are not available for the complete mixture.

Classification procedure

The method for classification of the mixture is based on ingredients of the mixture (additivity formula).

Classification acc. to GHS

Acute toxicity

Shall not be classified as acutely toxic.

Australia: en Page: 7 / 14



acc. to Safe Work Australia's Code of Practice for Labelling of Workplace
Hazardous Chemicals (under WHS Regulations)

Interflon Lube EP+ (Aerosol)

Version number: 6.5date of issueRevision: 2025-04-02Replaces version of: (5)2025-04-02

Acute toxicity estimate (ATE) of components			
Name of substance	CAS No	Exposure route	ATE
(Z)-N-methyl-N-(1-oxo-9-octadecenyl)glycine	110-25-8	inhalation: vapour	1.37 ^{mg} / _l /4h

Skin corrosion/irritation

Causes skin irritation.

Serious eye damage/eye irritation

Causes serious eye irritation.

Respiratory or skin sensitisation

Shall not be classified as a respiratory or skin sensitiser.

Germ cell mutagenicity

Shall not be classified as germ cell mutagenic.

Carcinogenicity

Shall not be classified as carcinogenic.

Reproductive toxicity

Shall not be classified as a reproductive toxicant.

Specific target organ toxicity - single exposure

May cause drowsiness or dizziness.

Specific target organ toxicity - repeated exposure

Shall not be classified as a specific target organ toxicant (repeated exposure).

Aspiration hazard

Shall not be classified as presenting an aspiration hazard.

SECTION 12: Ecological information

12.1 Toxicity

Toxic to aquatic life.

12.2 Persistence and degradability

Data are not available.

12.3 Bioaccumulative potential

Data are not available.

12.4 Mobility in soil

Data are not available.

12.5 Results of PBT and vPvB assessment

This mixture does not contain any substances that are assessed to be a PBT or a vPvB.

12.6 Endocrine disrupting properties

Does not contain an endocrine disruptor (ED) at a concentration of $\geq 0.1\%$.

12.7 Other adverse effects

Data are not available.

SECTION 13: Disposal considerations

13.1 Waste treatment methods

Sewage disposal-relevant information

Do not empty into drains.

Australia: en Page: 8 / 14



acc. to Safe Work Australia's Code of Practice for Labelling of Workplace
Hazardous Chemicals (under WHS Regulations)

Interflon Lube EP+ (Aerosol)

Version number: 6.5date of issueRevision: 2025-04-02Replaces version of: (5)2025-04-02

Waste treatment of containers/packagings

Only packagings which are approved (e.g. acc. to the Dangerous Goods Regulations) may be used. This article should be disposed of as hazardous waste. Please do not put it in your normal household waste. Dispose of this material and its container to hazardous or special waste collection point. Handle contaminated packages in the same way as the substance itself.

Relevant provisions relating to waste (Basel Convention)

Properties of waste which render it hazardous

H3 Flammable liquids

Remarks

Please consider the relevant national or regional provisions. Waste shall be separated into the categories that can be handled separately by the local or national waste management facilities.

SECTION 14: Transport information

14.1 UN number

UN 1950
IMDG-Code
UN 1950
ICAO-TI
UN 1950

14.2 UN proper shipping name

UN RTDG AEROSOLS IMDG-Code AEROSOLS

ICAO-TI Aerosols, flammable

14.3 Transport hazard class(es)

UN RTDG 2.1 IMDG-Code 2.1 ICAO-TI 2.1

14.4 Packing group not assigned

14.5 Environmental hazards non-environmentally hazardous acc. to the dan-

gerous goods regulations

14.6 Special precautions for user

There is no additional information.

14.7 Transport in bulk according to IMO instruments

The cargo is not intended to be carried in bulk.

Information for each of the UN Model Regulations

Transport information - National regulations - Additional information (UN RTDG)

UN number 1950
Class 2.1
Danger label(s) 2.1



Special provisions (SP) 63, 190, 277, 327, 344, 381, 959 (UN RTDG)

Australia: en Page: 9 / 14



acc. to Safe Work Australia's Code of Practice for Labelling of Workplace
Hazardous Chemicals (under WHS Regulations)

Interflon Lube EP+ (Aerosol)

Version number: 6.5date of issueRevision: 2025-04-02Replaces version of: (5)2025-04-02

Excepted quantities (EQ) E0 (UN RTDG)
Limited quantities (LQ) 1 L (UN RTDG)

International Maritime Dangerous Goods Code (IMDG) - Additional information

Marine pollutant Danger label(s) 2.1

2

Special provisions (SP) 63, 190, 277, 327, 344, 381, 959

Excepted quantities (EQ) E0
Limited quantities (LQ) 1 L
EmS F-D, S-U

Stowage category -

International Civil Aviation Organization (ICAO-IATA/DGR) - Additional information

Danger label(s) 2.1



Special provisions (SP) A145, A167

Excepted quantities (EQ) E0
Limited quantities (LQ) 30 kg

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture There is no additional information.

There is no additional information

National inventories

Country	Inventory	Status
CA	DSL	all ingredients are listed
EU	REACH Reg.	not all ingredients are listed
US	TSCA	all ingredients are listed

<u>Legend</u>

DSL Domestic Substances List (DSL)
REACH Reg. REACH registered substances
TSCA Toxic Substance Control Act

15.2 Chemical Safety Assessment

Chemical safety assessments for substances in this mixture were not carried out.

Australia: en Page: 10 / 14



acc. to Safe Work Australia's Code of Practice for Labelling of Workplace
Hazardous Chemicals (under WHS Regulations)

Interflon Lube EP+ (Aerosol)

Version number: 6.5date of issueRevision: 2025-04-02Replaces version of: (5)2025-04-02

SECTION 16: Other information

Indication of changes (revised safety data sheet)

Section	Former entry (text/value)	Actual entry (text/value)	Safety- relevant
1.3		Supplier (importer): Interflon Australia 13 Sigvard Blvd Hallam VIC 3803 Telephone: +61 402 522 112 Melvelle Equipment Australia +61 2 4951 5244 +61 2 4950 1291 Andrew@melvelle.com.au	yes
1.3	e-mail (competent person): Service@Interflon.com	e-mail (competent person): australia@interflon.com	yes
1.4		Poison centre: change in the listing (table)	yes
2.2		- Hazard statements: change in the listing (table)	yes
2.3		Results of PBT and vPvB assessment: Does not contain a PBT-/vPvB-substance at a concentration of ≥ 0,1%.	yes
2.3		Endocrine disrupting properties: Does not contain an endocrine disruptor (ED) at a concentration of ≥ 0,1%.	yes
3.2		Hazardous ingredients: change in the listing (table)	yes
3.2		Regulation 648/2004/EC on detergents	yes
3.2		Regulation 648/2004/EC on detergents: change in the listing (table)	yes
3.2		Remarks: For full text of Hazard- and EU Hazard-state- ments: see SECTION 16.	yes
5.1	Suitable extinguishing media: Water mist, Fire extinguishing powder	Suitable extinguishing media: Water spray, Water mist, Fire extinguishing powder, Carbon dioxide (CO2), Alcohol resistant foam	yes
5.2	Special hazards arising from the substance or mixture	Special hazards arising from the substance or mixture: In case of insufficient ventilation and/or in use, may form flammable/explosive vapour-air mix- ture.	yes
7.1	- Measures to prevent fire as well as aerosol and dust generation: Use local and general ventilation. Use only in well-ventilated areas.	- Measures to prevent fire as well as aerosol and dust generation: Use local and general ventilation. Take precautionary measures against static discharge. Use only in well-ventilated areas. Ground/bond container and receiving equipment.	yes
8.1		Occupational exposure limit values (Workplace Exposure Limits)	yes
8.2	Eye/face protection: Use safety goggle with side protection.	Eye/face protection: Work with safety glasses.	yes
8.2	Hand protection: Wear protective gloves. When handling with chemical substances, protective gloves must be	Hand protection: When handling with chemical substances, pro- tective gloves must be worn with the CE-label in-	yes

Australia: en Page: 11 / 14



acc. to Safe Work Australia's Code of Practice for Labelling of Workplace
Hazardous Chemicals (under WHS Regulations)

Interflon Lube EP+ (Aerosol)

Version number: 6.5date of issueRevision: 2025-04-02Replaces version of: (5)2025-04-02

Section	Former entry (text/value)	Actual entry (text/value)	Safety- relevant
	worn with the CE-label including the four control digits. Type of material. NBR: acrylonitrile-butadiene rubber. CR: chloroprene (chlorobutadiene) rubber. PVC: polyvinyl chloride.	cluding the four control digits. Type of material. NBR: acrylonitrile-butadiene rubber. CR: chloro- prene (chlorobutadiene) rubber. PVC: polyvinyl chloride.	
8.2	Respiratory protection: Type: A-P2 (combined filters against particles and organic gases and vapours, colour code: Brown/White).	Respiratory protection: [In case of inadequate ventilation] wear respirat- ory protection. Type: A-P2 (combined filters against particles and organic gases and vapours, colour code: Brown/White).	yes
9.1	pH (value): not determined	pH (value): not relevant	yes
9.1	Kinematic viscosity: not relevant	Kinematic viscosity: not determined	yes
9.2	Components (flammable): 44 %	Components (flammable): 44 % 44 % by mass of the contents are flammable	yes
12.6	Endocrine disrupting properties: None of the ingredients are listed.	Endocrine disrupting properties: Does not contain an endocrine disruptor (ED) at a concentration of ≥ 0,1%.	yes
13.1	Sewage disposal-relevant information: Do not empty into drains. Avoid release to the environment. Refer to special instructions/safety data sheets.	Sewage disposal-relevant information: Do not empty into drains.	yes
13.1	Waste treatment of containers/packagings: Only packagings which are approved (e.g. acc. to the Dangerous Goods Regulations) may be used. Completely emptied packages can be recycled. Handle contaminated packages in the same way as the substance itself.	Waste treatment of containers/packagings: Only packagings which are approved (e.g. acc. to the Dangerous Goods Regulations) may be used. This article should be disposed of as hazardous waste. Please do not put it in your normal house- hold waste. Dispose of this material and its con- tainer to hazardous or special waste collection point. Handle contaminated packages in the same way as the substance itself.	yes
16		Abbreviations and acronyms: change in the listing (table)	yes
16		List of relevant phrases (code and full text as stated in section 2 and 3): change in the listing (table)	yes

Abbreviations and acronyms

Abbr.	Descriptions of used abbreviations
Acute Tox.	Acute toxicity
Asp. Tox.	Aspiration hazard
ATE	Acute Toxicity Estimate
CAS	Chemical Abstracts Service (service that maintains the most comprehensive list of chemical substances)
Ceiling-C	Ceiling value
DGR	Dangerous Goods Regulations (see IATA/DGR)
DNEL	Derived No-Effect Level
ED	Endocrine disruptor
EmS	Emergency Schedule
Eye Dam.	Seriously damaging to the eye

Australia: en Page: 12 / 14



acc. to Safe Work Australia's Code of Practice for Labelling of Workplace
Hazardous Chemicals (under WHS Regulations)

Interflon Lube EP+ (Aerosol)

Version number: 6.5date of issueRevision: 2025-04-02Replaces version of: (5)2025-04-02

Abbr.	Descriptions of used abbreviations
Eye Irrit.	Irritant to the eye
Flam. Gas	Flammable gas
Flam. Liq.	Flammable liquid
GHS	"Globally Harmonized System of Classification and Labelling of Chemicals" developed by the United Nations
IATA	International Air Transport Association
IATA/DGR	Dangerous Goods Regulations (DGR) for the air transport (IATA)
ICAO	International Civil Aviation Organization
ICAO-TI	Technical instructions for the safe transport of dangerous goods by air
IMDG	International Maritime Dangerous Goods Code
IMDG-Code	International Maritime Dangerous Goods Code
PBT	Persistent, Bioaccumulative and Toxic
ppm	Parts per million
Press. Gas	Gas under pressure
Skin Corr.	Corrosive to skin
Skin Irrit.	Irritant to skin
STEL	Short-term exposure limit
STOT SE	Specific target organ toxicity - single exposure
TWA	Time-weighted average
UN RTDG	UN Recommendations on the Transport of Dangerous Good
vPvB	Very Persistent and very Bioaccumulative
WES	Safe Work Australia: Workplace exposure standards for airborne contaminants

Key literature references and sources for data

Safe Work Australia's Code of Practice for Labelling of Workplace Hazardous Chemicals (under WHS Regulations). UN Recommendations on the Transport of Dangerous Good. International Maritime Dangerous Goods Code (IMDG). Dangerous Goods Regulations (DGR) for the air transport (IATA).

Classification procedure

Physical and chemical properties: The classification is based on tested mixture.

Health hazards, Environmental hazards: The method for classification of the mixture is based on ingredients of the mixture (additivity formula).

List of relevant phrases (code and full text as stated in section 2 and 3)

Code	Text
H220	Extremely flammable gas.
H222	Extremely flammable aerosol.
H225	Highly flammable liquid and vapour.
H227	Combustible liquid.
H229	Pressurised container: may burst if heated.
H280	Contains gas under pressure; may explode if heated.
H304	May be fatal if swallowed and enters airways.
H315	Causes skin irritation.

Australia: en Page: 13 / 14



acc. to Safe Work Australia's Code of Practice for Labelling of Workplace
Hazardous Chemicals (under WHS Regulations)

Interflon Lube EP+ (Aerosol)

Version number: 6.5date of issueRevision: 2025-04-02Replaces version of: (5)2025-04-02

Code	Text
H318	Causes serious eye damage.
H319	Causes serious eye irritation.
H332	Harmful if inhaled.
H336	May cause drowsiness or dizziness.

Disclaimer

This information is based upon the present state of our knowledge. This SDS has been compiled and is solely intended for this product.

Australia: en Page: 14 / 14