

Interflon Metal Clean F (Aerosol)

Version number:
1.4

Date of issue
2026-02-17

Revision:
2026-02-17.

1 Identification

1.1 Product identifier

Trade name **Interflon Metal Clean F (Aerosol)**

1.2 Relevant identified uses of the substance or mixture and uses advised against

Relevant identified uses Industrial use
Scope cleaning agent

1.3 Details of the supplier of the safety data sheet

Interflon BV
Belder 47
4704 RK Roosendaal
Netherlands

Telephone: +31 (0)165 553911
e-mail: Service@Interflon.com
Website: www.Interflon.com

e-mail (competent person) Service@Interflon.com

1.4 Emergency telephone number

Poison center			
Name	Street	City	Telephone
Poison Control Center		Ontario	1-800-268-9017 24 hours a day, 7 days a week

2 Hazard identification

2.1 Classification of the substance or mixture

Classification acc. to GHS

Section	Hazard class	Category	Hazard class and category	Hazard statement
2.3	aerosols	1	Aerosol 1	H222,H229
3.2	skin corrosion/irritation	2	Skin Irrit. 2	H315
3.3	serious eye damage/eye irritation	2	Eye Irrit. 2	H319
3.8D	specific target organ toxicity - single exposure (narcotic effects, drowsiness)	3	STOT SE 3	H336

For full text of abbreviations: see SECTION 16.

2.2 Label elements

Labeling

- Signal word. danger

- Pictograms

GHS02, GHS07



Interflon Metal Clean F (Aerosol)

Version number: 1.4

date of issue
2026-02-17

Date of compilation: Revision: 2026-02-17

- Hazard statements
 - H222 Extremely flammable aerosol.
 - H229 Pressurized container: may burst if heated.
 - H315 Causes skin irritation.
 - H319 Causes serious eye irritation.
 - H336 May cause drowsiness or dizziness.

- Precautionary statements
 - P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
 - P211 Do not spray on an open flame or other ignition source.
 - P251 Do not pierce or burn, even after use.
 - P261 Avoid breathing dust/fume/gas/mist/vapours/spray.
 - P271 Use only outdoors or in a well-ventilated area.
 - P280 Wear protective gloves.
 - P302+P352 IF ON SKIN: Wash with plenty of water.
 - P304+P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing.
 - P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
 - P312 Call a POISON CENTER/doctor if you feel unwell.
 - P321 Specific treatment (see on this label).
 - P362+P364 Take off contaminated clothing and wash it before reuse.
 - P403+P233 Store in a well-ventilated place. Keep container tightly closed.
 - P405 Store locked up.
 - P410+P412 Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F.
 - P501 Dispose of contents/container in accordance with local/regional/national/international regulations.

- Hazardous ingredients for labelling

Isopropanol, Hydrocarbons, C7-C9, isoalkanes

2.3 Other hazards

This mixture does not contain any substances that are assessed to be a PBT or a vPvB.

Results of PBT and vPvB assessment

Does not contain a PBT-/vPvB-substance at a concentration of $\geq 0.1\%$.

Endocrine disrupting properties

Does not contain an endocrine disruptor (ED) in a concentration of $\geq 0.1\%$.

3 Composition/ Information on ingredients

3.1 Substances

Not relevant (mixture)

3.2 Mixtures

Product description

Mixture of solvents and additives

Hazardous ingredients

Name of substance	Identifier	Wt%	Classification acc. to GHS	Notes
Isopropanol	CAS No 67-63-0	30 - < 60	Flam. Liq. 2 / H225 Eye Irrit. 2 / H319 STOT SE 3 / H336	
Hydrocarbons, C7-C9, isoalkanes	CAS No 64741-66-8	30 - < 60	Flam. Liq. 2 / H225 Skin Irrit. 2 / H315 STOT SE 3 / H336 Asp. Tox. 1 / H304	P(a)
carbon dioxide	CAS No 124-38-9	1 - < 5	Press. Gas L / H280 sA 1 / H-sA	

Interflon Metal Clean F (Aerosol)

Version number: 1.4

date of issue
2026-02-17Date of compilation: Revi-
sion: 2026-02-17Notes

P(a): The classification as a carcinogen or mutagen is mandatory. The substance contains at least 0,1 % w/w benzene (EINECS No 200-753-7)

Remarks

For full text of Hazard- and EU Hazard-statements: see SECTION 16.

4 First-aid measures**4.1 Description of first-aid measures****General notes**

Do not leave affected person unattended. Remove victim out of the danger area. Keep affected person warm, still and covered. Take off immediately all contaminated clothing. In all cases of doubt, or when symptoms persist, seek medical advice. In case of unconsciousness place person in the recovery position. Never give anything by mouth.

Following inhalation

If breathing is irregular or stopped, immediately seek medical assistance and start first aid actions. In case of respiratory tract irritation, consult a physician. Provide fresh air.

Following skin contact

Wash with plenty of soap and water.

Following eye contact

Remove contact lenses, if present and easy to do. Continue rinsing. Irrigate copiously with clean, fresh water for at least 10 minutes, holding the eyelids apart.

Following ingestion

Rinse mouth with water (only if the person is conscious). Do NOT induce vomiting.

4.2 Most important symptoms and effects, both acute and delayed

Symptoms and effects are not known to date.

4.3 Indication of any immediate medical attention and special treatment needed

none

5 Fire-fighting measures**5.1 Extinguishing media****Suitable extinguishing media**

Water spray, Water mist, Alcohol resistant foam, Fire extinguishing powder, Carbon dioxide (CO₂), Alcohol resistant foam

Unsuitable extinguishing media

Water jet

5.2 Special hazards arising from the substance or mixture

In case of insufficient ventilation and/or in use, may form flammable/explosive vapor-air mixture.

Hazardous combustion products

Carbon monoxide (CO), Carbon dioxide (CO₂)

5.3 Advice for firefighters

In case of fire and/or explosion do not breathe fumes. Coordinate firefighting measures to the fire surroundings. Do not allow firefighting water to enter drains or water courses. Collect contaminated firefighting water separately. Fight fire with normal precautions from a reasonable distance. Use suitable breathing apparatus.

6 Accidental release measures**6.1 Personal precautions, protective equipment and emergency procedures****For non-emergency personnel**

Remove persons to safety.

For emergency responders

Interflon Metal Clean F (Aerosol)

Version number: 1.4

date of issue
2026-02-17

Date of compilation: Revi-
sion: 2026-02-17

Wear breathing apparatus if exposed to vapors/dust/aerosols/gases.

6.2 Environmental precautions

Keep away from drains, surface and ground water. Retain contaminated washing water and dispose of it. If substance has entered a water course or sewer, inform the responsible authority.

6.3 Methods and material for containment and cleaning up

Advice on how to contain a spill

Covering of drains

Other information relating to spills and releases

Place in appropriate containers for disposal. Ventilate affected area.

6.4 Reference to other sections

Hazardous combustion products: see section 5. Personal protective equipment: see section 8. Incompatible materials: see section 10. Disposal considerations: see section 13.

7 Handling and storage

7.1 Precautions for safe handling

Recommendations

- Measures to prevent fire as well as aerosol and dust generation

Use local and general ventilation. Take precautionary measures against static discharge. Use only in well-ventilated areas. Ground/bond container and receiving equipment.

Advice on general occupational hygiene

Remove contaminated clothing and protective equipment before entering eating areas. Never place chemicals in containers that are normally used for food or drink.

7.2 Conditions for safe storage, including any incompatibilities

Conditions of storage

Store in accordance with local/regional/national/international regulations. Keep container tightly closed and in a well-ventilated place.

Managing of associated risks

- Flammability hazards

Do not spray on an open flame or other ignition source. Protect from sunlight. Keep in a cool place.

- Packaging compatibilities

Only packagings which are approved (e.g. acc. to the Dangerous Goods Regulations) may be used.

7.3 Specific end use(s)

See section 16 for a general overview.

8 Exposure controls/ Personal protection

8.1 Control parameters

Occupational exposure limit values (Workplace Exposure Limits)

Occupational exposure limit values (Workplace Exposure Limits)											
Country	Name of agent	CAS No	Identifier	TWA [ppm]	TWA [mg/m³]	STEL [ppm]	STEL [mg/m³]	Ceiling-C [ppm]	Ceiling-C [mg/m³]	Notation	Source
CA	carbon dioxide	124-38-9	OEL (AB)	5,000	9,000	30,000	54,000				OHS Code
CA	carbon dioxide	124-38-9	OEL (BC)	5,000		15,000					"BC Regulation"
CA	carbon dioxide	124-38-9	OEL (ON-	5,000		30,000					MoL

Interflon Metal Clean F (Aerosol)

Version number: 1.4

date of issue
2026-02-17

Date of compilation: Revi-
sion: 2026-02-17

Occupational exposure limit values (Workplace Exposure Limits)											
Country	Name of agent	CAS No	Identifi- er	TWA [ppm]	TWA [mg/m ³]	STEL [ppm]	STEL [mg/m ³]	Ceiling-C [ppm]	Ceiling-C [mg/m ³]	Nota- tion	Source
			MoL)								
CA	carbon dioxide	124-38-9	PEV/VE A	5,000	9,000	30,000	54,000				Regula- tion OHS
CA	2-propanol	67-63-0	OEL (ON- MoL)	200		400					MoL
CA	2-propanol (isop- ropyl alcohol) (propan-2-ol)	67-63-0	OEL (AB)	200	492	400	984				OHS Code
CA	isopropanol (isop- ropyl alcohol) (2- propanol)	67-63-0	OEL (BC)	200		400					"BC Regula- tion"
CA	isopropyl alcohol	67-63-0	PEV/VE A	200		400					Regula- tion OHS

Notation

- Ceiling-C ceiling value is a limit value above which exposure should not occur
- STEL short-term exposure limit: a limit value above which exposure should not occur and which is related to a 15-minute period (unless otherwise specified)
- TWA time-weighted average (long-term exposure limit): measured or calculated in relation to a reference period of 8 hours
time-weighted average (unless otherwise specified)

Relevant DNELs of components						
Name of substance	CAS No	Endpoint	Threshold level	Protection goal, route of exposure	Used in	Exposure time
Isopropanol	67-63-0	DNEL	500 mg/m ³	human, inhalatory	worker (industry)	chronic - systemic effects
Isopropanol	67-63-0	DNEL	1,000 mg/m ³	human, inhalatory	worker (industry)	acute - systemic effects
Isopropanol	67-63-0	DNEL	888 mg/kg bw/day	human, dermal	worker (industry)	chronic - systemic effects
Hydrocarbons, C7-C9, isoalkanes	64741-66-8	DNEL	2,035 mg/m ³	human, inhalatory	worker (industry)	chronic - systemic effects
Hydrocarbons, C7-C9, isoalkanes	64741-66-8	DNEL	773 mg/kg bw/day	human, dermal	worker (industry)	chronic - systemic effects

Relevant PNECs of components						
Name of substance	CAS No	Endpoint	Threshold level	Organism	Environmental compartment	Exposure time
Isopropanol	67-63-0	PNEC	140.9 mg/l	aquatic organisms	freshwater	short-term (single instance)
Isopropanol	67-63-0	PNEC	140.9 mg/l	aquatic organisms	marine water	short-term (single instance)
Isopropanol	67-63-0	PNEC	2,251 mg/l	aquatic organisms	sewage treatment plant (STP)	short-term (single instance)
Isopropanol	67-63-0	PNEC	552 mg/kg	aquatic organisms	freshwater sediment	short-term (single instance)

Interflon Metal Clean F (Aerosol)

Version number: 1.4

date of issue
2026-02-17

Date of compilation: Revision: 2026-02-17

Relevant PNECs of components						
Name of substance	CAS No	Endpoint	Threshold level	Organism	Environmental compartment	Exposure time
Isopropanol	67-63-0	PNEC	552 mg/kg	aquatic organisms	marine sediment	short-term (single instance)
Isopropanol	67-63-0	PNEC	28 mg/kg	terrestrial organisms	soil	short-term (single instance)

8.2 Exposure controls

General safety precautions

Use only in well-ventilated areas.
In case of insufficient ventilation, wear suitable respiratory equipment.
Avoid contact with skin and eyes.
Keep away from food, drink and animal feedingstuffs. Do not breathe gas/vapor/spray. Wash hands after use.

Individual protection measures (personal protective equipment)

Eye/face protection

Work with safety glasses.

Skin protection

- Hand protection

When handling with chemical substances, protective gloves must be worn with the CE-label including the four control digits. Type of material. NBR: acrylonitrile-butadiene rubber. CR: chloroprene (chlorobutadiene) rubber. PVC: polyvinyl chloride.

- Other protection measures

Take recovery periods for skin regeneration. Preventive skin protection (barrier creams/ointments) is recommended. Wash hands thoroughly after handling.

Respiratory protection

[In case of inadequate ventilation] wear respiratory protection. Type: A-P2 (combined filters against particles and organic gases and vapors, color code: Brown/White).

Environmental exposure controls

Use appropriate container to avoid environmental contamination. Keep away from drains, surface and ground water.

9 Physical and chemical properties

9.1 Information on basic physical and chemical properties

Physical state	liquid, gaseous (spray aerosol)
Color	colorless
Odor	characteristic
Melting point/freezing point	<-20 °C
Boiling point or initial boiling point and boiling range	-44.5 °C
Flammability	flammable aerosol in accordance with GHS criteria
Lower and upper explosion limit	0.8 vol% - 7.7 vol% non-combustible
Flash point	-9 °C not relevant
Auto-ignition temperature	>200 °C (auto-ignition temperature (liquids and gases))

Interflon Metal Clean F (Aerosol)

Version number: 1.4

date of issue
2026-02-17

Date of compilation: Revision: 2026-02-17

Decomposition temperature	not relevant
pH (value)	not determined
Kinematic viscosity	$\leq 2.5 \text{ mm}^2/\text{s}$ at 20 °C not relevant not relevant

Solubility(ies) easily soluble

Water solubility	1 g/l at 20 °C
------------------	----------------

Partition coefficient

Partition coefficient n-octanol/water (log value)	not relevant
---	--------------

Vapor pressure	6,500 hPa at 20 °C
----------------	--------------------

Density and/or relative density

Density	0.66 g/cm ³ at 20 °C
Relative vapour density	information on this property is not available / not relevant

Particle characteristics	not relevant (aerosol)
--------------------------	------------------------

9.2 Other information

Information with regard to physical hazard classes	there is no additional information
--	------------------------------------

Other safety characteristics

Temperature class (USA, acc. to NEC 500)	T3 (maximum permissible surface temperature on the equipment: 200°C)
--	--

10 Stability and reactivity

10.1 Reactivity

Concerning incompatibility: see below "Conditions to avoid" and "Incompatible materials". The mixture contains reactive substance(s). Risk of ignition.

10.2 Chemical stability

See below "Conditions to avoid".

10.3 Possibility of hazardous reactions

No known hazardous reactions.

10.4 Conditions to avoid

Do not spray on an open flame or other ignition source. Keep away from heat.

Hints to prevent fire or explosion

Protect from sunlight.

10.5 Incompatible materials

Interflon Metal Clean F (Aerosol)

Version number: 1.4

date of issue
2026-02-17

Date of compilation: Revision: 2026-02-17

Oxidizers

10.6 Hazardous decomposition products

Hazardous combustion products: see section 5.

11 Toxicological information

11.1 Information on toxicological effects

Test data are not available for the complete mixture.

Classification procedure

The method for classification of the mixture is based on ingredients of the mixture (additivity formula).

Classification acc. to GHS

Acute toxicity

Shall not be classified as acutely toxic.

Acute toxicity of components					
Name of substance	CAS No	Exposure route	Endpoint	Value	Species
Hydrocarbons, C7-C9, isoalkanes	64741-66-8	oral	LD50	>7,100 – 7,800 mg/kg	rat

Skin corrosion/irritation

Causes skin irritation.

Serious eye damage/eye irritation

Causes serious eye irritation.

Respiratory or skin sensitization

Shall not be classified as a respiratory or skin sensitizer.

Germ cell mutagenicity

Shall not be classified as germ cell mutagenic.

Carcinogenicity

Shall not be classified as carcinogenic.

Reproductive toxicity

Shall not be classified as a reproductive toxicant.

Specific target organ toxicity - single exposure

May cause drowsiness or dizziness.

Specific target organ toxicity - repeated exposure

Shall not be classified as a specific target organ toxicant (repeated exposure).

Aspiration hazard

Shall not be classified as presenting an aspiration hazard.

12 Ecological information

12.1 Toxicity

Very toxic to aquatic life with long lasting effects.

Aquatic toxicity (acute) of components of the mixture

Aquatic toxicity (acute) of components					
Name of substance	CAS No	Endpoint	Value	Species	Exposure time
Isopropanol	67-63-0	LC50	10,000 mg/l	fish	96 h
Hydrocarbons, C7-C9,	64741-66-8	LL50	18.4 mg/l	fish	96 h

Interflon Metal Clean F (Aerosol)

Version number: 1.4

date of issue
2026-02-17

Date of compilation: Revision:
2026-02-17

Aquatic toxicity (acute) of components					
Name of substance	CAS No	Endpoint	Value	Species	Exposure time
isoalkanes					
Hydrocarbons, C7-C9, isoalkanes	64741-66-8	LC50	0.11 mg/l	fish	96 h
Hydrocarbons, C7-C9, isoalkanes	64741-66-8	EL50	2.4 mg/l	aquatic invertebrates	48 h
Hydrocarbons, C7-C9, isoalkanes	64741-66-8	EC50	0.4 mg/l	aquatic invertebrates	48 h

Aquatic toxicity (chronic) of components of the mixture

Aquatic toxicity (chronic) of components					
Name of substance	CAS No	Endpoint	Value	Species	Exposure time
Hydrocarbons, C7-C9, isoalkanes	64741-66-8	EL50	1.6 mg/l	aquatic invertebrates	21 d
Hydrocarbons, C7-C9, isoalkanes	64741-66-8	EC50	0.23 mg/l	aquatic invertebrates	21 d

12.2 Persistence and degradability

Data are not available.

12.3 Bioaccumulative potential

Data are not available.

12.4 Mobility in soil

Data are not available.

12.5 Results of PBT and vPvB assessment

This mixture does not contain any substances that are assessed to be a PBT or a vPvB.

12.6 Endocrine disrupting properties

Does not contain an endocrine disruptor (ED) in a concentration of $\geq 0.1\%$.

12.7 Other adverse effects

Data are not available.

13 Disposal considerations

13.1 Waste treatment methods

Sewage disposal-relevant information

Do not empty into drains.

Waste treatment of containers/packages

Only packagings which are approved (e.g. acc. to the Dangerous Goods Regulations) may be used. This article should be disposed of as hazardous waste. Please do not put it in your normal household waste. Dispose of this material and its container to hazardous or special waste collection point. Handle contaminated packages in the same way as the substance itself.

Relevant provisions relating to waste (Basel Convention)

Properties of waste which render it hazardous

H3 Flammable liquids

Remarks

Interflon Metal Clean F (Aerosol)

Version number: 1.4

date of issue
2026-02-17

Date of compilation: Revision: 2026-02-17

Please consider the relevant national or regional provisions. Waste shall be separated into the categories that can be handled separately by the local or national waste management facilities.

14 Transport information

14.1 UN number

UN RTDG	UN 1950
IMDG-Code	UN 1950
ICAO-TI	UN 1950

14.2 UN proper shipping name

UN RTDG	AEROSOLS
IMDG-Code	AEROSOLS
ICAO-TI	Aerosols, flammable

14.3 Transport hazard class(es)

UN RTDG	2.1
IMDG-Code	2.1
ICAO-TI	2.1

14.4 Packing group

not assigned

14.5 Environmental hazards

Environmentally hazardous substance (aquatic environment)	hazardous to the aquatic environment Hydrocarbons, C7-C9, isoalkanes
---	---

14.6 Special precautions for user

There is no additional information.

14.7 Transport in bulk according to IMO instruments

The cargo is not intended to be carried in bulk.

Information for each of the UN Model Regulations

Transport information - National regulations - Additional information (UN RTDG)

UN number	1950
Class	2.1
Environmental hazards	yes (hazardous to the aquatic environment)
Danger label(s)	2.1



Special provisions (SP)	63, 190, 277, 327, 344, 381, 959 (UN RTDG)
Excepted quantities (EQ)	E0 (UN RTDG)
Limited quantities (LQ)	1 L (UN RTDG)

International Maritime Dangerous Goods Code (IMDG) - Additional information

Marine pollutant	yes (hazardous to the aquatic environment)
Danger label(s)	2.1

Interflon Metal Clean F (Aerosol)

Version number: 1.4

date of issue
2026-02-17

Date of compilation: Revi-
sion: 2026-02-17



Special provisions (SP)	63, 190, 277, 327, 344, 381, 959
Excepted quantities (EQ)	E0
Limited quantities (LQ)	1 L
EmS	F-D, S-U
Stowage category	-

International Civil Aviation Organization (ICAO-IATA/DGR) - Additional information

Environmental hazards	yes (hazardous to the aquatic environment)
Danger label(s)	2.1



Special provisions (SP)	A145, A167
Excepted quantities (EQ)	E0
Limited quantities (LQ)	30 kg

15 Regulatory information

15.1 Safety, health and environmental regulations specific for the product in question

National regulations (United States)

Toxic Substance Control Act (TSCA)	all ingredients are listed (ACTIVE) or exempt from listing
---	--

Superfund Amendment and Reauthorization Act (SARA TITLE III)

- The List of Extremely Hazardous Substances and Their Threshold Planning Quantities (EPCRA Section 302, 304)
none of the ingredients are listed
- Specific Toxic Chemical Listings (EPCRA Section 313)

Toxics Release Inventory: Specific Toxic Chemical Listings			
Name of substance	CAS No	Remarks	Effective date
Isopropanol	67-63-0	only persons who manufacture by the strong acid process are subject, supplier notification not required	1987-01-01

Comprehensive Environmental Response, Compensation, and Liability Act (CERCLA)

- List of Hazardous Substances and Reportable Quantities (CERCLA section 102a) (40 CFR 302.4)
none of the ingredients are listed

Clean Air Act

none of the ingredients are listed

Right to Know Hazardous Substance List

Interflon Metal Clean F (Aerosol)

Version number: 1.4

date of issue
2026-02-17

Date of compilation: Revi-
sion: 2026-02-17

- Hazardous Substance List (NJ-RTK)

Name of substance	CAS No	Remarks	Classifications
Isopropanol	67-63-0		F3
carbon dioxide	124-38-9		

Legend

F3 Flammable - Third Degree

California Environmental Protection Agency (Cal/EPA): Proposition 65 - Safe Drinking Water and Toxic Enforcement Act of 1987

none of the ingredients are listed

Industry or sector specific available guidance(s)

NPCA-HMIS® III

Hazardous Materials Identification System. American Coatings Association.

Category	Rating	Description
Chronic	*	chronic (long-term) health effects may result from repeated overexposure
Health	2	temporary or minor injury may occur
Flammability	1	material that must be preheated before ignition can occur
Physical hazard	0	material that is normally stable, even under fire conditions, and will not react with water, polymerize, decompose, condense, or self-react. Non-explosive
Personal protection	-	

NFPA® 704

National Fire Protection Association: Standard System for the Identification of the Hazards of Materials for Emergency Response (United States).

Category	Degree of hazard	Description
Flammability	1	material that must be preheated before ignition can occur
Health	2	material that, under emergency conditions, can cause temporary incapacitation or residual injury
Instability	0	material that is normally stable, even under fire conditions
Special hazard		

National regulations (Canada)

Domestic Substances List (DSL)

All ingredients are listed.

National inventories

Country	Inventory	Status
CA	DSL	all ingredients are listed
EU	REACH Reg.	all ingredients are listed
US	TSCA	all ingredients are listed (ACTIVE)
AU	AIIC	all ingredients are listed
CN	IECSC	all ingredients are listed

Interflon Metal Clean F (Aerosol)

Version number: 1.4

date of issue
2026-02-17

Date of compilation: Revision:
2026-02-17

Country	Inventory	Status
EU	ECSI	all ingredients are listed
JP	CSCL-ENCS	not all ingredients are listed
JP	ISHA-ENCS	not all ingredients are listed
KR	KECI	all ingredients are listed
MX	INSQ	not all ingredients are listed
NZ	NZIoC	all ingredients are listed
PH	PICCS	all ingredients are listed
TR	CICR	all ingredients are listed
TW	TCSI	all ingredients are listed

Legend

AIIC	Australian Inventory of Industrial Chemicals
CICR	Chemical Inventory and Control Regulation
CSCL-ENCS	List of Existing and New Chemical Substances (CSCL-ENCS)
DSL	Domestic Substances List (DSL)
ECSI	EC Substance Inventory (EINECS, ELINCS, NLP)
IECSC	Inventory of Existing Chemical Substances Produced or Imported in China
INSQ	National Inventory of Chemical Substances
ISHA-ENCS	Inventory of Existing and New Chemical Substances (ISHA-ENCS)
KECI	Korea Existing Chemicals Inventory
NZIoC	New Zealand Inventory of Chemicals
PICCS	Philippine Inventory of Chemicals and Chemical Substances (PICCS)
REACH Reg.	REACH registered substances
TCSI	Taiwan Chemical Substance Inventory
TSCA	Toxic Substance Control Act

15.2 Chemical Safety Assessment

Chemical safety assessments for substances in this mixture were not carried out.

16 Other information

Indication of changes (revised safety data sheet)

Section	Former entry (text/value)	Actual entry (text/value)	Safety-relevant
1.2		Relevant identified uses: Industrial use	yes
2.3	Results of PBT and vPvB assessment: Does not contain a PBT-/vPvB-substance in a concentration of $\geq 0.1\%$.	Results of PBT and vPvB assessment: Does not contain a PBT-/vPvB-substance at a concentration of $\geq 0.1\%$.	yes
3.2		Hazardous ingredients: change in the listing (table)	yes
3.2	Regulation 648/2004/EC on detergents		yes
3.2		Regulation 648/2004/EC on detergents: change in the listing (table)	yes
3.2		Remarks: For full text of Hazard- and EU Hazard-statements: see SECTION 16.	yes
5.1	Suitable extinguishing media: Water mist, Alcohol resistant foam, Fire extinguishing powder	Suitable extinguishing media: Water spray, Water mist, Alcohol resistant foam, Fire extinguishing powder, Carbon dioxide (CO ₂),	yes

Interflon Metal Clean F (Aerosol)

Version number: 1.4

date of issue
2026-02-17

Date of compilation: Revision: 2026-02-17

Section	Former entry (text/value)	Actual entry (text/value)	Safety-relevant
		Alcohol resistant foam	
5.2	Special hazards arising from the substance or mixture	Special hazards arising from the substance or mixture: In case of insufficient ventilation and/or in use, may form flammable/explosive vapor-air mixture.	yes
7.1	- Measures to prevent fire as well as aerosol and dust generation: Use local and general ventilation. Use only in well-ventilated areas.	- Measures to prevent fire as well as aerosol and dust generation: Use local and general ventilation. Take precautionary measures against static discharge. Use only in well-ventilated areas. Ground/bond container and receiving equipment.	yes
8.1	Occupational exposure limit values (Workplace Exposure Limits): not relevant	Occupational exposure limit values (Workplace Exposure Limits)	yes
8.1		Occupational exposure limit values (Workplace Exposure Limits): change in the listing (table)	yes
8.2	Hand protection: Wear protective gloves. Chemical protection gloves are suitable, which are tested according to EN 374. Type of material. NBR: acrylonitrile-butadiene rubber. CR: chloroprene (chlorobutadiene) rubber. PVC: polyvinyl chloride.	Hand protection: When handling with chemical substances, protective gloves must be worn with the CE-label including the four control digits. Type of material. NBR: acrylonitrile-butadiene rubber. CR: chloroprene (chlorobutadiene) rubber. PVC: polyvinyl chloride.	yes
8.2	Respiratory protection: Type: A-P2 (combined filters against particles and organic gases and vapors, color code: Brown/White).	Respiratory protection: [In case of inadequate ventilation] wear respiratory protection. Type: A-P2 (combined filters against particles and organic gases and vapors, color code: Brown/White).	yes
9.1	Lower and upper explosion limit: 0.8 vol% - 7.7 vol%	Lower and upper explosion limit: 0.8 vol% - 7.7 vol% non-combustible	yes
9.1	Flash point: -9 °C	Flash point: -9 °C not relevant	yes
9.1	Kinematic viscosity: ≤2.5 mm ² /s at 20 °C not relevant	Kinematic viscosity: ≤2.5 mm ² /s at 20 °C not relevant not relevant	yes
9.1	Solubility(ies)	Solubility(ies): easily soluble	yes
9.1	Partition coefficient n-octanol/water (log value): this information is not available	Partition coefficient n-octanol/water (log value): not relevant	yes
9.1	Density: 0.662 g/cm ³ at 20 °C	Density: 0.66 g/cm ³ at 20 °C	yes
9.1	Relative vapour density: information on this property is not available	Relative vapour density: information on this property is not available / not relevant	yes
9.2	Information with regard to physical hazard classes	Information with regard to physical hazard classes: there is no additional information	yes
9.2	Aerosols		yes
9.2	Components (flammable): 98.5 % 98.5 % by mass of the contents are flammable		yes
11.1		Acute toxicity of components: change in the listing (table)	yes
12.1		Aquatic toxicity (acute) of components of the mixture	yes

Interflon Metal Clean F (Aerosol)

Version number: 1.4

date of issue
2026-02-17

Date of compilation: Revision:
2026-02-17

Section	Former entry (text/value)	Actual entry (text/value)	Safety-relevant
12.1		Aquatic toxicity (acute) of components: change in the listing (table)	yes
12.1		Aquatic toxicity (chronic) of components of the mixture	yes
14.7	Danger label(s): 2.1, fish and tree	Danger label(s): 2.1	yes
14.7	Danger label(s): 2.1, fish and tree	Danger label(s): 2.1	yes
15.1	Clean Air Act	Clean Air Act: none of the ingredients are listed	yes
15.1		Clean Air Act: change in the listing (table)	yes
15.1		Hazardous Substance List (NJ-RTK): change in the listing (table)	yes
15.1		NPCA-HMIS® III: change in the listing (table)	yes
15.1		NFPA® 704: change in the listing (table)	yes
16		Abbreviations and acronyms: change in the listing (table)	yes
16		List of relevant phrases (code and full text as stated in section 2 and 3): change in the listing (table)	yes

Abbreviations and acronyms

Abbr.	Descriptions of used abbreviations
"BC Regulation"	OHS Regulation: Section 5.48 (British Columbia)
Asp. Tox.	Aspiration hazard
CAS	Chemical Abstracts Service (service that maintains the most comprehensive list of chemical substances)
Ceiling-C	Ceiling value
DGR	Dangerous Goods Regulations (see IATA/DGR)
DNEL	Derived No-Effect Level
EC50	Effective Concentration 50 %. The EC50 corresponds to the concentration of a tested substance causing 50 % changes in response (e.g. on growth) during a specified time interval
ED	Endocrine disruptor
EINECS	European Inventory of Existing Commercial Chemical Substances
EL50	Effective Loading 50 %: the EL50 corresponds to the loading rate required to produce a response in 50% of the test organisms
ELINCS	European List of Notified Chemical Substances
EmS	Emergency Schedule
Eye Dam.	Seriously damaging to the eye
Eye Irrit.	Irritant to the eye
Flam. Liq.	Flammable liquid
GHS	"Globally Harmonized System of Classification and Labelling of Chemicals" developed by the United Nations

Interflon Metal Clean F (Aerosol)

Version number: 1.4

date of issue
2026-02-17

Date of compilation: Revision: 2026-02-17

Abbr.	Descriptions of used abbreviations
IATA	International Air Transport Association
IATA/DGR	Dangerous Goods Regulations (DGR) for the air transport (IATA)
ICAO	International Civil Aviation Organization
ICAO-TI	Technical instructions for the safe transport of dangerous goods by air
IMDG	International Maritime Dangerous Goods Code
IMDG-Code	International Maritime Dangerous Goods Code
LC50	Lethal Concentration 50%: the LC50 corresponds to the concentration of a tested substance causing 50 % lethality during a specified time interval
LD50	Lethal Dose 50 %: the LD50 corresponds to the dose of a tested substance causing 50 % lethality during a specified time interval
LL50	Lethal Loading 50 %: the LL50 corresponds to the loading rate causing 50 % lethality
MoL	Ministry of Labor: Current Occupational Exposure Limits for Ontario Workplaces Required under Regulation 833
NLP	No-Longer Polymer
NPCA-HMIS® III	National Paint and Coatings Association: Hazardous Materials Identification System - HMIS® III, Third Edition
OHS Code	Occupational Health and Safety Code: Occupational exposure limits for chemical substances (Alberta)
PBT	Persistent, Bioaccumulative and Toxic
PNEC	Predicted No-Effect Concentration
ppm	Parts per million
Press. Gas	Gas under pressure
Regulation OHS	Regulation respecting occupational health and safety: Permissible exposure values for airborne contaminants (Quebec)
RTECS	Registry of Toxic Effects of Chemical Substances (database of NIOSH with toxicological information)
sA	Simple asphyxiants
Skin Corr.	Corrosive to skin
Skin Irrit.	Irritant to skin
STEL	Short-term exposure limit
STOT SE	Specific target organ toxicity - single exposure
TWA	Time-weighted average
UN RTDG	UN Recommendations on the Transport of Dangerous Good
vPvB	Very Persistent and very Bioaccumulative

Key literature references and sources for data

Hazardous Products Regulations (HPR)
 SOR/2022-272: Regulations Amending the Hazardous Products Regulations (GHS, Seventh Revised Edition)
 UN Recommendations on the Transport of Dangerous Good. International Maritime Dangerous Goods Code (IMDG).
 Dangerous Goods Regulations (DGR) for the air transport (IATA).

Classification procedure

Physical and chemical properties: The classification is based on tested mixture.
 Health hazards, Environmental hazards: The method for classification of the mixture is based on ingredients of the mixture (additivity formula).

Interflon Metal Clean F (Aerosol)

Version number: 1.4

date of issue
2026-02-17Date of compilation: Revi-
sion: 2026-02-17**List of relevant phrases (code and full text as stated in section 2 and 3)**

Code	Text
H-sA	May displace oxygen and cause rapid suffocation.
H222	Extremely flammable aerosol.
H225	Highly flammable liquid and vapour.
H229	Pressurized container: may burst if heated.
H280	Contains gas under pressure; may explode if heated.
H304	May be fatal if swallowed and enters airways.
H315	Causes skin irritation.
H319	Causes serious eye irritation.
H336	May cause drowsiness or dizziness.

Disclaimer

This information is based upon the present state of our knowledge. This SDS has been compiled and is solely intended for this product.