

Technical Data Sheet

Interflon Food Lube 3H (aerosol)

Synthetic multipurpose lubricant and release agent for NSF-3H direct food contact

Interflon Food Lube 3H is a release agent on solid surfaces, based on edible synthetic ester oil of vegetable origin enforced with MicPol® Technology. It is specially developed for applications in the food processing industry. Provides protection against adherence during food processing, as well as against rust and corrosion. Extends useful life for problem-free operation in environments where applications are in regular contact with water, and or where higher processing temperatures are being applied. It is suited as a NSF-H1 lubricant at medium speeds and moderate loads, and can be used throughout the food processing operation where direct or indirect contact with the food may occur.

Interflon Food Lube 3H (aerosol) is 3H and H1 listed by the NSF for use in applications where food contact is allowed according to FDA 21 CFR 178.3570 CFR and FDA 21 CFR 178.3620.

Applications

Interflon Food Lube 3H (aerosol) is suitable as release agent on solid surfaces in ovens, pans, meat & boning benches, chop boards and other surfaces with food contact. May also be used for lubrication and protection of machine components such as rollers, chains, knives, wheels, slides and guides. Providing lubrication beyond any NSF-3H registered product available in the market. None to low deposit formation at elevated temperatures. Formulated with edible-grade ingredients* to fully comply with direct food contact requirements. Unlike conventional 3H release agents, Interflon Food Lube 3H (aerosol) has a very wide temperature range and allows prolonged relubricating intervals at elevated temperatures without the undesired formation of deposits.

*Interflon Food Lube 3H (aerosol) is not registered as edible but contains individual ingredients that are Generally Recognized As Safe (GRAS).

Advantages

- Complies with both FDA 21 CFR 178.3570 and FDA CFR 178.3620
- Long lasting compared to traditional release agents
- Releases and lubricates
- No buildup of hard residues when exposed to high temperatures
- Good protection against corrosion
- Does not contain any allergens according to regulation EU 1169/2011
- Does not contain GMO (Genetically Modified Organisms)
- Aerosol can also be used in an upside down (vertical) position
- Non-toxic, odourless and tasteless
- PFAS free
- MOSH-MOAH free*

*Interflon Food Lube 3H (aerosol) is formulated free of harmful MOSH MOAH components. Distinguishing MOSH from synthetic components or harmless mineral content with the current available analyzing techniques is not 100% accurate. Therefore, profound knowledge of raw materials is required.

Instructions for use

Shake well before use. Use aerosol from a vertical (upright or upside down) position only. Parts should be cleaned first with a solvent or alkaline cleaning agent. Wipe off the excess with a clean cloth.

Note: do not use too much Interflon Food Lube 3H (aerosol). A thin layer, with occasional re-application now and again, works better than a thick layer.

Property	Result	Method
Composition	Edible synthetic ester oil of vegetable origin, additives and MicPol®.	
Colour	Light yellow	
Density 20°C	0,73 g/cm3	
Pour point	-10°C	
Lowest application temperature	-5°C	
Highest application temperature	160°C	
Manufacturing date	The batch number consists of a 8-digit number. The first 4 numbers represent the YY/MM of the manufacturing.	
Shelf life*	4 years	
Base oil viscosity 40°C	33 cSt	DIN 51801
ISO VG	32	
NSF registration number	173074	
NSF	3H, H1	
Halal	Yes	
Kosher	Yes	
Vegan	Yes	

* Shelf life of the product in original and unopened packaging. Storage temperatures <0°C need to be avoided to guarantee product quality.

This information is based on our best and present knowledge and intended to provide general notes about the product and intended use. Therefore it shouldn't be construed as guaranteeing properties of the product described or suitability for an application. Any existing industrial property rights must be observed. Quality of our products is guaranteed under our General Conditions of Sale. Interflon® and MicPol® are registered trademarks of Interflon BV. Typical properties mentioned in this document are based on our production tolerances and do not represent a specification. Variations that do not affect product performance are to be expected during normal manufacturing. Information provided in this document is subject to change without notice in advance.